

EP DIN 13000 TE



Generator :

	3~ 400V	1~ 230V
Standby output (kVA):	12,5	1x4kVA on 1 socket or 12kVA divided over the 3 schuko sockets
Cont. output (kVA):	12	1x3.6kVA on 1 socket or 11kVA divided over the 3 schuko sockets
Amps (continu):	17,3	1x16A on 1 socket or 3x16A divided over the 3 schuko sockets
Dimensions in cm (l x w x h):	82 x 44 x 58	
Dry weight (kg):	150	

Engine:

Brand / Type:

Power:	BRIGGS & STRATTON VANGUARD 23 HP 14,8 kW (3000 rpm), gasoline, 2-cylinder, air-cooled
Displacement:	627 cm ³
Consumption (at 75% load) for generator use:	4,5 litres/hour
Tank:	10 liter
Autonomy (at 75% load):	2,2 hours
Starter:	Electric start (12V) / Battery 24Ah / recoil starter
Noise level at 75% load at 7m for generator use:	74 dB(A)/7m
Equipment:	Oil pressure sensor (engine shut down)

Alternator:

Brand / Type:

Nominal voltage:	SINCRO / SSG132 LA2-R – synchronous – brushless – IP54 – with AVR 3~ 400V / 1~ 230V
Frequency:	50 Hz (3000 rpm)

Arguments:

- Generating set with high quality VANGUARD 23HP gasoline engine
- Sincro alternator – brushless – IP54 – with AVR
- Compliant to DIN14685
- 4 lifting handles
- Hinged engine protection covers
- Large – easy to fill fuel tank 10 litre
- Toolbox with spare parts
 - o spark plug wrench
 - o open-end wrench 10-11 / 12-13mm
 - o oil filter
 - o fuel filter
 - o air cleaner element
 - o 2 spark plugs
- Maintenance: fuel filter, oil filter, air cleaner element, oil filler cap, oil/fuel drain are easily accessible
- Control panel:
 - o 1 socket 5pole 16A – IP67 / 3 sockets schuko 2pole 16A – IP68
 - o Thermal magnetic protection for every socket
- Control panel light 12V
 - o Earth tester with indicator lamp + test cable 1m
 - o Power meter with maximum indicator
 - o Hour counter
 - o V-meter
 - o Start – Stop button

Options:

- o Insulation protection
- o Flexible exhaust extension 2m (adapter for muffler included)
- o 12V connector for external battery start
- o 20L jerrycan and quick couplings
- o 3-way fuel cock with quick couplings for connection to external fuel tank
- o Other options on request

Hoffmann
Werkzeughandel

Bahnhofstraße 9
56736 Kottenheim
Telefon: 0 26 51 - 490 311
Telefax: 0 26 51 - 705 388

www.hoffmann-werkzeughandel.de

